


High-frequency Solenoid Valve PHF Series



How to Order

PHF	0830-8	1	E4
Series No.	Type No.	Port Quantity	Voltage
PHF	0830-8	1	E4 DC24V
	1618-16	2	E9 DC48V
	0918-9	3	
	0915-9	4	
	0913-9	8	
	0818-8	9	
	0815-8	16	
	0813-8		

Specifications

Model	Drive Voltage	Hold Voltage	Peak Current	Operating Pressure	Resistance	Gas Flow Rate	Valve Opening Time	Closing Speed	Medium	Frequency
PHF0830-8-1	DC 48V	DC 8V	14.4A	0.3 ~ 0.7Mpa	28Ω	4000L/min	1.5ms	1ms	Air	20 ~ 300Hz
PHF0830-8-2	DC 48V	DC 8V	7.2A	0.3 ~ 0.7Mpa	28Ω	2000L/min	1.5ms	1ms	Air	20 ~ 300Hz
PHF0830-8-4	DC 48V	DC 8V	3.6A	0.3 ~ 0.7Mpa	28Ω	1000L/min	1.5ms	1ms	Air	20 ~ 300Hz
PHF0830-8-8	DC 48V	DC 8V	1.8A	0.3 ~ 0.7Mpa	28Ω	500L/min	1.5ms	1ms	Air	20 ~ 300Hz
PHF1618-16-4	DC 24V	DC 5V	3.2A	0.3 ~ 0.7Mpa	28Ω	800L/min	1.0ms	0.5ms	Air	20 ~ 300Hz
PHF1618-16-8	DC 24V	DC 5V	1.6A	0.3 ~ 0.7Mpa	28Ω	400L/min	1.0ms	0.5ms	Air	20 ~ 300Hz
PHF1618-16-16	DC 24V	DC 5V	0.8A	0.1 ~ 0.7Mpa	28Ω	100L/min	1.0ms	0.5ms	Air	20 ~ 300Hz
PHF0918-9	DC 24V	DC 5V	0.8A	0.1 ~ 0.7Mpa	28Ω	100L/min	1.0ms	0.6ms	Air	20 ~ 300Hz
PHF0918-9-3	DC 24V	DC 5V	2.4A	0.1 ~ 0.7Mpa	28Ω	300L/min	1.0ms	0.6ms	Air	20 ~ 300Hz
PHF0915-9	DC 24V	DC 5V	0.8A	0.1 ~ 0.7Mpa	28Ω	70L/min	0.6ms	0.6ms	Air	20 ~ 300Hz
PHF0913-9	DC 24V	DC 5V	0.8A	0.1 ~ 0.7Mpa	28Ω	40L/min	1.0ms	0.6ms	Air	20 ~ 300Hz
PHF0818-8-4	DC 24V	DC 5V	1.6A	0.1 ~ 0.7Mpa	28Ω	400L/min	1.0ms	0.6ms	Air	20 ~ 300Hz
PHF0818-8-2	DC 24V	DC 5V	3.2A	0.1 ~ 0.7Mpa	28Ω	800L/min	0.6ms	0.6ms	Air	20 ~ 300Hz
PHF0815-8	DC 24V	DC 5V	0.8A	0.1 ~ 0.7Mpa	28Ω	100L/min	1.0ms	0.6ms	Air	20 ~ 300Hz
PHF0813-8	DC 24V	DC 5V	0.8A	0.1 ~ 0.7Mpa	28Ω	50L/min	1.0ms	0.6ms	Air	20 ~ 300Hz