

How to Order

PSV ——— **Z** ——— **15** **S** ——— **E4**

Series No.

Structure

Z	Right-Angle
Y	Submerged

Diameter

15	G1/2"
20	G3/4"
25	G1"
35	G1 1/4"
40	G1 1/2"
50	G2"
62	G2 1/2"
76	G3"

Type

Blank	Single Diaphragm
S	Double Diaphragm
P	Square Type
J	Economical Type
D	Dual Inlet Pipe Type
F	Flange Type

Voltage

E2	AC220V
E1	AC110V
E4	DC24V

Temperature Level

Blank	-25°C ~ 80°C
T1	-25°C ~ 150°C
T2	-25°C ~ 230°C

Specifications

Diameter	Φ15	Φ20	Φ25	Φ35	Φ40	Φ50	Φ62	Φ76
Port Size	G1/2"	G3/4"	G1"	G1 1/4"	G1 1/2"	G2"	G2 1/2"	G3"
Working Pressure	0.3 ~ 0.8 MPa							
Working Temperature	-5 ~ 55 °C							
Relative Humidity	< 85%							
Working Medium	Clean Air							
Voltage	AC110V / AC220V / DC24V							
Current	0.46A / 0.23A / 0.8A ± 10%							
Ingress Protection	Ip65							



● Right-Angle Pulse valve



● Submerged Pulse valve



● Square Type Pulse valve



● Flange Type



● Dual Inlet Pipe Type