

How to Order

Series No. A C 20 00 01 D R J 1 5M G

Type No.

C	Filter+regulator+lubricator
W	Filter+regulator
F	Filter
R	Regulator
L	Lubricator

Body Size

10	1000 body
20	2000 body
30	3000 body
40	4000 body
50	5000 body

Combination

10	Two units
00	Others

Port Size

1000	M5
2000	01:1/8"
3000	02:1/4"
4000	03:3/8"
5000	04:1/2"

Drain Type

Blank	Semi-auto drain
D	Auto Drain type

Pressure Gauge

R	With Round Pressure Gauge
S	With Square Pressure Gauge
N	No Pressure Gauge

Bracket

Blank	With bracket
J	No bracket

Scale Unit

1	Mpa/Bar
2	Bar/Psi
3	Mpa/Psi

Filter Precision

Blank	25 μm
5M	5 μm

ThreadType

G	BSPP thread
P	BSPT thread
T	NPT thread

Specifications

Body Size	1000	2000	3000	4000	5000
Guaranteed Pressure (MPa)	1.5				
Working Pressure (MPa)	0.15 ~ 1.0				
Pressure Adjustment Range(MPa)	0.05 ~ 0.9				
Working Temperature(°C)	-5 ~ 60				
Filter Precision	25µm(5 µm is optional)				
Recommended Oil	Turbine No.1 Oil ISOVG32				
Bowl Material	Polycarbonate				
Bowl Guard	None		Available		
Valve Type	With overflow				

- AC1000-M5 ● AC4000-03
- AC2000-01 ● AC4000-04
- AC2000-02 ● AC4000-06
- AC3000-02 ● AC5000-06
- AC3000-03 ● AC5000-10

- AL1000-M5 ● AL4000-03
- AL2000-01 ● AL4000-04
- AL2000-02 ● AL4000-06
- AL3000-02 ● AL5000-06
- AL3000-03 ● AL5000-10

- AF1000-M5 ● AF4000-03
- AF2000-01 ● AF4000-04
- AF2000-02 ● AF4000-06
- AF3000-02 ● AF5000-06
- AF3000-03 ● AF5000-10

- AR1000-M5 ● AR4000-03
- AR2000-01 ● AR4000-04
- AR2000-02 ● AR4000-06
- AR3000-02 ● AR5000-06
- AR3000-03 ● AR5000-10

How to Order

Series No. AN C 20 00 01 R 1

Type No.

C	Filter+regulator+lubricator
W	Filter+regulator
F	Filter
R	Regulator
L	Lubricator

Combination

10	Two units
00	Others

Body Size

20	2000 body
30	3000 body
40	4000 body
50	5000 body

Drain Type

Blank	Semi-auto drain
D	Auto Drain type

Pressure Gauge

R	With Round Pressure Gauge
S	With Square Pressure Gauge
N	No Pressure Gauge

Bracket

Blank	With bracket
J	No bracket

Scale Unit

1	Mpa/Bar
2	Bar/Psi
3	Mpa/Psi

Filter Precision

Blank	25 μm
5M	5 μm

ThreadType

G	BSPP thread
P	BSPT thread
T	NPT thread

Port Size

2000	02	1/4"
3000	02	1/4"
3000	03	3/8"
4000	04	1/2"

Specifications

Body Size	2000	3000	4000	5000
Guaranteed Pressure (MPa)	1.5			
Working Pressure Range(MPa)	0.15 ~ 1.0			
Pressure Adjustment Range(MPa)	0.05 ~ 0.9			
Working temperature(°C)	-5 ~ 60			
Filter precision	25μm(5 μm is optional)			
Recommended oil	Turbine No.1 Oil ISOVG32			
Bowl material	Polycarbonate			
Valve type	With overflow			

- ANC2000-02
- ANC3000-02
- ANC3000-03
- ANC4000-04

- ANL2000-02
- ANL3000-02
- ANL3000-03
- ANL4000-04

- ANW2000-02
- ANW3000-02
- ANW3000-03
- ANW4000-04

- ANF2000-02
- ANF3000-02
- ANF3000-03
- ANF4000-04

AM Series (Metal Cup)

